



75 Size		W U-Dimension		0750 Thread		Lagging		H Shank		T Type		260 Bore		C Material		Cap & Chain		Facing		Rating		Special Lagging Length	
Code	Inches	Code	Inches	Code	Inches	Code	Inches	Code	Type	Code	Type	Code	Type	Code	Type	Code	Facing	Code	Rating #	Code	Rating #		
50	1/2	0162	1 1/8	-	Without	T	NPT Thd.	260	.260"	AA	Brass	1	Brass	F	Flat Face	150	150						
75	3/4	0250	2 1/2	L	With	W	Weld-in	385	.385"	B	Carbon Steel	2	Stainless Steel	R	Raised Face	300	300						
10	1	0450	4 1/2			F	Flanged			C	AISI 304			J	Ring Joint	600	600						
12	1 1/4	0750	7 1/2			V	Van Stone			S	AISI 316			L	Lap Joint	1500	1500						
15	1 1/2	1050	10 1/2			S	Socket Weld			M	Limited Space Threaded					2500	2500						
20	2	1350	13 1/2			G	Ground Joint			C	Sanitary												
30	3	1650	16 1/2																				
40	4	1950	19 1/2																				
		2250	22 1/2																				

**Type:** Straight (Uniform) Shank, Threaded  
**Bore Size:** .385  
**Process Conn.:** 1/2, 3/4, 1 NPT, Wed-In  
**Materials:** Brass, Carbon Steel  
 304 Stainless Steel, 316 Stainless Steel




Standard Configuration




Lagging Configuration

**Type:** Stepped Shank, Threaded  
**Bore Size:** .260  
**Process Conn.:** 1/2, 3/4, 1 NPT  
**Materials:** Brass, Carbon Steel  
 304 Stainless Steel, 316 Stainless Steel



Standard Configuration




Lagging Configuration

**Type:** Tapered Shank, Threaded  
**Bore Size:** .260, .385  
**Process Conn.:** 1/2, 3/4, 1 NPT  
**Materials:** Brass, Carbon Steel  
 304 Stainless Steel, 316 Stainless Steel




Standard Configuration




Lagging Configuration

**Type:** Socket Weld  
**Bore Size:** .260, .385  
**Process Conn.:** 3/4, 1" Pipe Size  
**Materials:** 304 Stainless Steel, 316 Stainless Steel,  
 Carbon Steel




Standard Configuration




Lagging Configuration

**Type:** Van Stone  
**Bore Size:** .260, .385  
**Process Conn.:** 1, 1 1/2" Pipe Size  
**Materials:** 304 Stainless Steel, 316 Stainless Steel




Standard Configuration

**Type:** Weld-in  
**Bore Size:** .260, .385  
**Process Conn.:** 1 1/2" Dia.  
**Materials:** 304 Stainless Steel, 316 Stainless Steel




Standard Configuration

**Type:** Flanged  
**Bore Size:** .260, .385  
**Process Conn.:** 1, 1 1/2, 2" Pipe Size  
**Materials:** 304 Stainless Steel, 316 Stainless Steel



Standard Configuration

**Type:** Sanitary  
**Bore Size:** .260, .385  
**Process Conn.:** Tri-Clamp connection® 1, 1 1/2, 2"  
**Materials:** 304 Stainless Steel, 316 Stainless Steel



Standard Configuration



Lagging Configuration

*Consult factory for guidance in product selection  
 Phone (203) 378-8281, Fax (203) 385-0499 or  
 visit our web site at [www.ashcroft.com](http://www.ashcroft.com)*